

DEGREASER 3600

1.931.3600

ANTISILICONE DEGREASER

Antisilicone **Degreaser 3600** is a preparation product especially designed to remove dirt, oils, waxes, silicone and other contaminant agents from bare metal areas before painting. It performs very well at all temperatures and with any kind of job. It facilitates preparatory work on large areas.

USE

Apply generously with a clean cloth. While area is still wet, dry with another clean dry cloth.
Degrease one part/area at a time, avoiding treatment of different areas at the same time.
Be careful not to allow the degreaser to dry on the substrate.

Note:

The use of an ultrafine Scotch Brite soaked with antisilicone degreaser 3600 is strongly recommended for maximum effectiveness.



TECHNICAL DATA

Pack size 1 and 5 l
Storage store in cool dry place away from heat

VOC INFORMATION

The EU limit value for this product (product category: IIB.a) in ready to use form is max. 850g/litre of VOC
The VOC content of this product in ready to use form is max. 850g/litre.
Depending on the chosen mode of use, the actual ready to use VOC of this product may be lower than that specified by the EU directive code.

SAFETY AND HANDLING

These products are for professional use only and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

For Health and Safety information, please refer to the material Safety Data Sheet, also available at :
http://www.ppg.com/Maxmeyer_MSDS

For further information please contact:
PPG Industries (UK) Limited.
MaxMeyer Division
Customer Service & Sales Group,
Nedham Road,
Stowmarket,
Suffolk.
IP14 2AD,
England.
Tel: 01449 771779
Fax: 01449 773495

